

Specification Sheet

BF1503

COATED MATT PAPER FSC

S2000N



FACE:

A specially coated matt white woodfree printing paper with a smooth and micro-porous surface structure designed for colour ink jet printing. Designed specifically for VP ink jet digital printer from VIP Color Tech. This product is suitable for a wide range of industrial applications, where on demand colour coding, or picture coding is required. FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, LicenceCode:C004451).

Thickness 110 micron $\pm 5\%$

Basic weight 92 gsm $\pm 5\%$

ADHESIVE:

S2000 An acrylic based permanent adhesive with excellent adhesive performance on a wide variety of flat and curved substrates including packaging materials such as cardboard, plastic films, and PE and PP containers. Labels can also be used successfully on chilled products, dry substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +80°C

UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 54 micron $\pm 5\%$

Basic Weight 61 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.