

# Specification Sheet

BF158

LASER COPY JET PREMIUM FSC

S2012HT



## FACE:

A matt white woodfree machine finished paper with good opacity and excellent absorbtion, plus superior toner-bonding characteristics. The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451)

Thickness 77 micron  $\pm 5\%$

Basic weight 67 gsm  $\pm 5\%$

## ADHESIVE:

S2012HT A permanent modified acrylic aqueous dispersion. Specially designed for roll to sheet conversion, e.g. for copier and laser printer products. Combines reduced edge bleed with high cardboard adhesion. For this adhesive, we would recommend stripping of the sheets.

Initial Tack High

Final Adhesion High

Min. App.Temp 0°C

Temp Range -20°C to +80°C

UV Resistance Good

Complies with FDA 175.105 and BgVV XIV recommendations for direct contact with dry, moist and non fatty foodstuff.

## LINER:

A lightweight woodfree, white kraft paper, based on TFC pulp. For applications where good layflatness and dimensional stability are required. Suitable for converting rolls into sheets and for low medium laser printers.

Thickness 54 micron  $\pm 5\%$

Basic Weight 51 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.