

# Specification Sheet

BF159

LASER COPY JET PREMIUM FSC

LR2



## FACE:

A matt white woodfree machine finished paper with good opacity and excellent absorbtion, plus superior toner-bonding characteristics. The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451)

Thickness 72 micron  $\pm 5\%$

Basic weight 64 gsm  $\pm 5\%$

## ADHESIVE:

LR2 A special purpose removable, acrylic based adhesive Offering good initial tack and excellent removability when used with laser, copier and inkjet facematerials. The adhesive has good UV resistance and relatively long term removability.

Initial Tack Low

Final Adhesion Low

Min. App.Temp  $-15^{\circ}\text{C}$

Temp Range  $-30^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry, moist and non-fatty foodstuff.

## LINER:

A lightweight woodfree, white kraft paper, based on TFC pulp. For applications where good layflatness and dimensional stability are required. Suitable for converting rolls into sheets and for low medium laser printers.

Thickness 60 micron

Basic Weight 55 gsm

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.