

# Specification Sheet

BF188

FASTRANSFER PLUS CHILL FSC

S2045N



## FACE:

A specially-coated, extra white, woodfree printing paper with an even smoother micro-absorbent surface structure. Compatibility with a wide range of wax and wax-resin, thermal transfer ribbons. Excellent print resolution of picket fence and rotated barcodes. Thermal transfer print speeds up to 225 mm/sec. Superb multicolour printing results. Application include: inventory, address and shelf edge labels. . FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, LicenceCode:C004451).

Thickness 77 micron  $\pm 5\%$

Basic weight 85 gsm  $\pm 5\%$

## ADHESIVE:

S2045 A rubber based, permanent adhesive. Excellent adhesive performance on a wide variety of substrates including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures, eg labelling of chilled products. Excellent conversion characteristics.

Initial Tack High

Final Adhesion Very high

Min. App.Temp  $-5^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$

UV Resistance Poor

Complies with FDA 175.105 and with BgVV XXI recommendations for direct contact with dry and moist non-fatty foodstuff.

## LINER:

A supercalendered siliconised honey glassine paper, with high mechanical resistance to tearing.

Thickness 51 micron  $\pm 5\%$

Basic Weight 57 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.