

# Specification Sheet

BF192

DIRECT THERMAL ECO PERM FSC

S2000N



## FACE:

A white woodfree printing paper with a high sensitivity thermal coating providing good image resolution. This thermosensitive product is designed for use in thermal printing systems at printing speeds up to 250 mm/sec. (based on printers set up). FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, LicenceCode:C004451).

Thickness 80 micron  $\pm 5\%$

Basic weight 78 gsm  $\pm 5\%$

## ADHESIVE:

S2000N An acrylic based permanent adhesive with excellent adhesive performance on a wide variety of flat and curved substrates including packaging materials such as cardboard, plastic films, and PE and PP containers.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +50°C

UV Resistance N/A

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

## LINER:

A supercalendered honey glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 55 micron  $\pm 5\%$

Basic Weight 60 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.