

Specification Sheet

BF228

DIGI UVIJ RUSTIQUE CREME

S2030



FACE:

A Cream, uncoated matt woodfree printing paper with felt marked finish. Wet strength and fungicidal treatments. This paper has a specific topcoating for excellent image quality and ink anchorage using the UV inkjet process

Thickness 130 micron $\pm 5\%$

Basic weight 90 gsm $\pm 5\%$

ADHESIVE:

The adhesive features high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates. Specially designed for wine labelling applications it allows easy conversion of difficult label shapes

Initial Tack Very

Final Adhesion Very high

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -20°C to $+80^{\circ}\text{C}$

UV Resistance Moderate

Complies with FDA 175.105 and the German recommendations XXI as published by BfR for direct contact with dry and moist non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron $\pm 5\%$

Basic Weight 70 gsm $\pm 5\%$

SHELF LIFE:

1 year when stored at $22^{\circ} \pm 2^{\circ}\text{C}$ / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.