

Specification Sheet

BF631

ULTRADESTRUCTIBLE SEMI GLOSS PVC

S2000N



FACE:

A "frangible" semi gloss white cast PVC film.

The product is designed with extreme tamper evidence as a priority. The heavily filled face is highly frangible, of low caliper - giving little "edge" to pick at - and conformable/semi squeezable to avoid accidental breakage after application.

Thickness 60 micron \pm 5%

Basic weight 112 gsm \pm 5%

ADHESIVE:

S2000N - A general purpose permanent acrylic based adhesive.

UL Approved.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +80°C

UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

Conversion - It is recommended that corners are designed with as large a radius as is practical to facilitate matrix stripping.

LINER:

A supercalendered machine readable white glassine paper, with high mechanical resistance to tearing and excellent smoothness.

Thickness 69 micron \pm 5%

Basic Weight 80 gsm \pm 5%

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.