

Specification Sheet

BF857

FLEXSECURE SILVER VOID

S697



FACE:

A matt silver top coated polyester, with an easy peel dry void effect, suitable for printing by all conventional methods including thermal transfer. Once applied to the substrate on removal, an irreversible and dry "void" footprint message will detach itself from the face film. It is suitable for a wide range of substrates including paper and fabric

Thickness 62 micron $\pm 5\%$

Basic weight 81 gsm $\pm 5\%$

ADHESIVE:

S697 - A permanent, acrylic based adhesive with a very good initial tack and adhesion on a wide range of substrates. Excellent clarity and UV resistance

Initial Tack High

Final Adhesion High

Min. App.Temp $+10^{\circ}\text{C}$

Temp Range -20°C to $+80^{\circ}\text{C}$

UV Resistance Excellent

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 62 micron $\pm 5\%$

Basic Weight 73 gsm $\pm 5\%$

SHELF LIFE:

1 year when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.