

Specification Sheet

BM1006

DIRECT THERMAL MATT WHITE PP
HIGH TACK



FACE:

A white BOPP film, coated with a black imaging thermosensitive coating. Designed for use in thermal printing systems. Applications include barcode labels for pallet wrap, airline baggage tags and retail labels for frozen foods.

Thickness 76 micron $\pm 5\%$
Basic weight 61 gsm $\pm 5\%$

ADHESIVE:

A general purpose permanent, rubber based adhesive. The adhesive performs well at lower temperatures particularly on the labelling of chilled products.

Initial Tack High
Final Adhesion Very high
Min. App.Temp 0°C
Temp Range -40°C to +70°C
UV Resistance Poor

Complies with FDA 175.105 and with BgVV XXI recommendations for direct contact with dry and moist non-fatty foodstuff.

LINER:

A supercalendered glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 51 micron $\pm 5\%$
Basic Weight 57 gsm $\pm 5\%$

SHELF LIFE:

1 year when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.