

# Specification Sheet

BM1015A

GLOSS CLEAR C.I. PET "VOID" FTP REVEAL  
PERMANENT



## FACE:

A gloss clear top coated polyester film with a covert "VOID" feature. Once applied to the substrate, an irreversible "VOID" footprint message will detach from the face film. Used for security applications where the label is required to provide evidence of tampering by leaving an adhesive "footprint" Once removed, it is not possible to replace the label without subsequent detection. Void text is visible under UV light.

Thickness 52 micron  $\pm 5\%$

Basic weight 72 gsm  $\pm 5\%$

## ADHESIVE:

An acrylic based permanent adhesive with high final adhesion on a wide range of substrates. The adhesive is perfectly adapted for uses that need very high label transparency.

Initial Tack High

Final Adhesion High

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+90^{\circ}\text{C}$

UV Resistance Good

We would strongly recommend that tests are carried out in real conditions of use and approved by customers, especially when labelling varnished carton boards, rough or apolar surfaces.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 62 micron  $\pm 5\%$

Basic Weight 73 gsm  $\pm 5\%$

## SHELF LIFE:

1 year when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.