

Specification Sheet

BM1019A

GLOSS WHITE C.I. PET "VOID" FTP REVEAL
PERMANENT



FACE:

A gloss white top coated polyester film with a covert "VOID" feature. Once applied to the substrate, an irreversible "VOID" footprint message will detach from the face film. Used for security applications where the label is required to provide evidence of tampering by leaving an adhesive "footprint". Once removed, it is not possible to replace the label without subsequent detection.

Thickness 60 micron \pm 5%

Basic weight 82 gsm \pm 5%

ADHESIVE:

A permanent acrylic based adhesive. Suitable for a wide range of substrates especially for applications that require good UV & solvent resistance.

Initial Tack High

Final Adhesion High

Min. App.Temp +5°C

Temp Range -40°C to +90°C

UV Resistance Good

We would strongly recommend that tests are carried out in real conditions of use and approved by customers, especially when labelling varnished carton boards, rough or apolar surfaces.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron \pm 5%

Basic Weight 74 gsm \pm 5%

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.