

# Specification Sheet

BM1182

MATT SILVER PET VOID

PERMANENT



## FACE:

A matt silver void polyester film with a selective release system for use in tamper evident labels. Exceeding the face surface temperature may cause the void mechanism to fail. Can be printed by flexography, screen, letterpress and offset. Special inks designed for non absorbent material should be used. Thermal transfer with selected ribbons.

Thickness 52 micron  $\pm 5\%$

Basic weight 71 gsm  $\pm 5\%$

## ADHESIVE:

A permanent modified acrylic aqueous dispersion.

Initial Tack Good

Final Adhesion High

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$

UV Resistance Good

Isega approved for direct contact with dry, moist and fatty foods.

## LINER:

White High Transparent glassine backing paper, specially developed for filmic label materials giving the best conversion properties.

Thickness 56 micron  $\pm 5\%$

Basic Weight 64 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.