

# Specification Sheet

BM1183

GLOSS SILVER PET VOID CHEQUERBOARD  
PERMANENT



## FACE:

A top coated gloss silver metallised polyester film with a void checkerboard pattern. Specifically designed for security applications where the label is required to provide evidence of tampering by leaving adhesive "checkerboard" pattern once removed. It is not possible to replace the label without detection. Printable by flexo, letterpress, offset and thermal transfer printing.

Thickness 52 micron  $\pm 5\%$   
Basic weight 71 gsm  $\pm 5\%$

## ADHESIVE:

A strong permanent acrylic based adhesive.

Initial Tack High  
Final Adhesion High  
Min. App.Temp  $+5^{\circ}\text{C}$   
Temp Range  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$   
UV Resistance Moderate

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 54 micron  $\pm 5\%$   
Basic Weight 61 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.