

# Specification Sheet

BM1184

GLOSS CLEAR PET VOID CHEQUERBOARD  
PERMANENT



## FACE:

Clear Gloss top coated polyester void with chequerboard pattern. Used for security applications where the label is required to provide evidence of tampering by leaving adhesive "chequerboard" pattern once removed. It is not possible to replace the label without detection.

Thickness 50 micron  $\pm 5\%$   
Basic weight 71 gsm  $\pm 5\%$

## ADHESIVE:

A UV acrylic permanent

Initial Tack High  
Final Adhesion High  
Min. App.Temp  $+5^{\circ}\text{C}$   
Temp Range  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$   
UV Resistance Good

## LINER:

White High Transparnt glassine backing paper,Specially developed for filmic label material.

Thickness 56 micron  $\pm 5\%$   
Basic Weight 64 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.