

# Specification Sheet

BM1204

MC80 SEMI GLOSS DIGI PAPER FSC

R5000N



## FACE:

A white semi gloss woodfree paper surface treated for Indigo digital printing. The facestock is made from FSC certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

Thickness 76 micron  $\pm 5\%$

Basic weight 80 gsm  $\pm 5\%$

## ADHESIVE:

R5000 A general purpose removable, acrylic based adhesive. The adhesive features good tack and adhesion in combination with superior and clean removability from most substrates. Good long term removability. Not recommended for use on porous substrates or for prolonged UV exposure

Initial Tack Low

Final Adhesion Low

Min. App.Temp  $-15^{\circ}\text{C}$

Temp Range  $-30^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

UV Resistance Poor

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 53 micron  $\pm 5\%$

Basic Weight 59 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.