

# Specification Sheet

BM1208

VELVET LEXAN POLYCARBONATE 75MM  
PERMANENT



## FACE:

A clear polycarbonate mark resistant over-laminating film. This film provides the ultimate label protection. Polycarbonate is impact, dirt, scuff resistant, whilst being resistant to mineral acids, hydro carbons, oils and greases.

Thickness 75 micron  $\pm 5\%$

Basic weight 81 gsm  $\pm 5\%$

## ADHESIVE:

A clear permanent, pressure sensitive acrylic adhesive.

Initial Tack Good

Final Adhesion High

Min. App.Temp  $+10^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+100^{\circ}\text{C}$

UV Resistance N/A

UL Approved.

## LINER:

A one-side silicone coated super clear polyester film.

Thickness 36 micron  $\pm 5\%$

Basic Weight 51 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.