

Specification Sheet

BM1214

INKJET GLOSS PAPER

PERMANENT



FACE:

A coated gloss white woodfree paper designed specifically for "photo quality" Ink Jet printing. Also printable by all conventional printing techniques including UV flexo, Offset UV, gravure and thermal transfer printing.

Thickness 100 micron $\pm 10\%$

Basic weight 85 gsm $\pm 10\%$

ADHESIVE:

A permanent acrylic adhesive with high clarity and cohesion with strong adhesion to apolar substrates.

Initial Tack High

Final Adhesion High

Min. App.Temp -5°C

Temp Range -40°C to $+120^{\circ}\text{C}$

UV Resistance Good

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

LINER:

A one side siliconised white glassine paper.

Thickness 55 micron $\pm 10\%$

Basic Weight 62 gsm $\pm 10\%$

SHELF LIFE:

1 year when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.