

Specification Sheet

BM296

GLOSS WHITE STATIC PE 110MM

SELF CLING



FACE:

A Gloss white co-extruded corona treated Polyethylene film. It is printable by all standard methods including UV offset, UV flexo, letterpress and UV screen process.

Thickness 110 micron $\pm 5\%$

Basic weight

ADHESIVE:

Cling film that clings without adhesive on smooth and glossy surfaces. It can be removed easily and leaves no residue. It can also be reapplied / reused.

Warning: If UV Lamps are too high the static element of the material will fail and print receptivity will be effected.

Initial Tack

Final Adhesion

Min. App.Temp +5°C

Temp Range -20°C to +50°C

UV Resistance

Complies with EN71/3 Toys Application and RoHS 2011/65/EU

LINER:

A supercalendered polycoated white glassine paper, with high mechanical resistance to tearing.

Thickness 100 micron $\pm 5\%$

Basic Weight 114 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.