

# Specification Sheet

BM320

BRIGHT SILVER PET 23MM PR

PERMANENT



## FACE:

A metallised polyester, top coated to be print receptive. For applications requiring a high quality metallised look on a low caliper material.

Thickness 23 micron  $\pm 5\%$

Basic weight 33 gsm  $\pm 5\%$

## ADHESIVE:

A permanent, acrylic aqueous, dispersion with good adhesion on glass and other substrates except for apolar PE, PP.

Initial Tack Medium

Final Adhesion High

Min. App.Temp  $+10^{\circ}\text{C}$

Temp Range  $-20^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$

UV Resistance Very good

BGVV compliance for indirect contact with foodstuffs.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 77 micron  $\pm 5\%$

Basic Weight 90 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.