Specification Sheet

BM359
SUPERCLEAR PET 75MM
PERMANENT

FACE:
A gloss super clear polyester film without top coating. Combined with a transparent Polyester liner, provides optimum smoothness to the adhesive, for a super clear finish.

Thickness	75 micron ±5%
Basic weight	104 gsm ±5%

ADHESIVE:
An extra permanent acrylic based adhesive with very good initial tack. This adhesive is suitable for a wide range of substrates.

Initial Tack	High
Final Adhesion	Very high
Min. App.Temp	+5°C
Temp Range	-40°C to +90°C
UV Resistance	Good

LINER:
A clear siliconised Polyester liner.

Thickness	23 micron ±5%
Basic Weight	32 gsm ±5%

SHELF LIFE:
2 years when stored at 22* C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.

Unit A2 Hubert Road, Brentwood, Essex CM14 4JE
Tel: 01277 281 910 Fax:0800 085 6992
sales@bakermaterials.co.uk www.bakermaterials.co.uk

REGISTRATION NO. 1116854 IN ENGLAND
REGISTERED OFFICE:UNIT A2 HUBERT ROAD BRENTWOOD ESSEX CM14 4JE
VAT Registration No. GB 230 7578 65