

Specification Sheet

BM401

LASER COPY JET

PEELABLE



FACE:

A matt white woodfree machine finished paper, with good opacity and excellent absorption, plus superior toner-bonding characteristics.

Thickness 72 micron $\pm 5\%$

Basic weight 64 gsm $\pm 5\%$

ADHESIVE:

A special purpose removable, acrylic based adhesive.

Initial Tack Low

Final Adhesion Low

Min. App.Temp -15°C

Temp Range -30°C to $+80^{\circ}\text{C}$

UV Resistance Good

This product is designed for the manufacture of A4 sheets for use in laser printers, copiers and inkjet printers.

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry, moist and non-fatty foodstuff.

LINER:

A lightweight woodfree white kraft paper.

Thickness 60 micron $\pm 5\%$

Basic Weight 55 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22 $^{\circ}$ C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.