

Specification Sheet

BM407

MATT SILVER LASER PET
PERMANENT



FACE:

A matt silver top coated polyester film. The face can be printed by letterpress, flexo, gravure and screen, giving excellent results with solvent, UV curing and water based inks and can be overprinted using dot matrix and thermal transfer. Hardened cutting dies are recommended.

Thickness 36 micron $\pm 5\%$

Basic weight 54 gsm $\pm 5\%$

ADHESIVE:

A clear permanent adhesive, featuring very good weatherability and UV resistance with good adhesion even on apolar substrates.

Initial Tack High

Final Adhesion High

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -20°C to $+80^{\circ}\text{C}$

UV Resistance Excellent

The adhesive complies with FDA 175.105 and with BgVV recommendations for direct contact with dry and moist, non-fatty foodstuff.

LINER:

A white one sided siliconised kraft paper, that has layflat qualities and can be back-printed.

Thickness 108 micron $\pm 5\%$

Basic Weight 100 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.