

Specification Sheet

BM424

VELVET LEXAN POLYCARBONATE 125MM
PERMANENT



FACE:

A transparent polycarbonate mark resistant over-laminating film. This film provides the ultimate label protection. Polycarbonate (PC) is impact, dirt, scuff and weather resistant, whilst being resistant to mineral acids, hydro carbons, oils and greases.

Thickness 125 micron \pm 5%
Basic weight

ADHESIVE:

A high performance permanent acrylic adhesive. It has a low initial tack and is suitable for hand application as it is initially repositionable. A permanent bond is formed within 30 minutes of application.

Initial Tack Low
Final Adhesion High
Min. App.Temp +5°C
Temp Range -40°C to +100°C
UV Resistance N/A

UL approved.

LINER:

A one side siliconised polyester film giving optimum smoothness to the adhesive layer.

Thickness 36 micron \pm 5%
Basic Weight

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.