

Specification Sheet

BM500
VELLUM 80
PERMANENT



FACE:

A white, surface sized, super-calendered wood free printing paper.
A basic general purpose, low cost paper suitable for a wide variety of applications.

Thickness 69 micron $\pm 5\%$
Basic weight 73 gsm $\pm 5\%$

ADHESIVE:

A modified, permanent, acrylic dispersion. A strong, permanent adhesive for general use in product and information labelling. Very good adhesion on a wide variety of substrates.

Initial Tack High
Final Adhesion Very high
Min. App.Temp 0°C
Temp Range -20°C to +80°C
UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry or moist non-fatty foodstuff.

LINER:

A supercalendered honey glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 55 micron $\pm 5\%$
Basic Weight 60 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.