

Specification Sheet

BM503

VELLUM 80 LAYFLAT

PERMANENT



FACE:

A white, surface sized, super-calendered wood free printing paper.
A basic general purpose, low cost paper suitable for a wide variety of applications.

Thickness 67 micron $\pm 5\%$

Basic weight 72 gsm $\pm 5\%$

ADHESIVE:

A modified, permanent, acrylic dispersion. A strong, permanent adhesive for general use in product and information labelling. Very good adhesion on a wide variety of substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +80°C

UV Resistance Good

LINER:

A white one sided siliconised kraft paper, that has layflat qualities and can be back-printed making it suitable for conversion to A4 sheets.

Thickness 82 micron $\pm 5\%$

Basic Weight 88 gsm $\pm 5\%$

SHELF LIFE:

4 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.