

Specification Sheet

BM522GR
RADIANT GREEN LITHO
PERMANENT



FACE:

Fluorescent green coated woodfree paper. Mainly used for promotional work, product identification, and price marking plus a wide range of miscellaneous uses where a background colour giving maximum visual impact is demanded for a long or short runs.

Thickness 66 micron $\pm 5\%$
Basic weight 68 gsm $\pm 5\%$

ADHESIVE:

A permanent, acrylic based adhesive with good adhesion on a wide variety of surfaces including apolar substrates like PE and PP.

Initial Tack High
Final Adhesion High
Min. App.Temp $+5^{\circ}\text{C}$
Temp Range -40°C to $+100^{\circ}\text{C}$
UV Resistance Good

Complies with ISEGA, FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 55 micron $\pm 5\%$
Basic Weight 62 gsm $\pm 5\%$

SHELF LIFE:

3 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.