

Specification Sheet

BM539
TYVEK
PERMANENT



FACE:

A matt white spun bonded polyolefin with high strength properties. This material is printable by flexographic and letterpress processes. It is tear resistant, unaffected by most chemicals and will withstand extremes of weather, abrasions and rough handling.

Thickness 210 micron $\pm 5\%$
Basic weight 75 gsm $\pm 5\%$

ADHESIVE:

A acrylic permanent, water based adhesive. Specifically designed for labelling of HDPE drums and other rough substrates.

Initial Tack High
Final Adhesion Very high
Min. App.Temp 0°C
Temp Range -20°C to +70°C
UV Resistance Moderate

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

LINER:

A supercalendered siliconised honey glassine paper, with high mechanical resistance to tearing.

Thickness 53 micron $\pm 5\%$
Basic Weight 60 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 20° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.