

# Specification Sheet

BM627

ULTRADESTRUCTIBLE PVC

PERMANENT



## FACE:

A matt white, ultradestructible, cast polyvinyl chloride (PVC) film with low tear strength. The product is designed with extreme tamper evidence as a priority.

Thickness 60 micron  $\pm$  5%

Basic weight 112 gsm  $\pm$ 5%

## ADHESIVE:

A permanent, solvent acrylic adhesive featuring good initial tack and ultimate adhesion on a wide range of substrates- plus high durability to solvents, UV and ageing.

UL Approved.

Initial Tack Very high

Final Adhesion Very high

Min. App.Temp +10°C

Temp Range -50°C to +110°C

UV Resistance Very good

Used for a variety of security applications and closure systems this product is extremely difficult to "waste strip" and labels are best presented "waste left in". It is however recommended that this material be trialled on all applications. It is recommended that corners are designed with as large a radius as is practical to facilitate matrix stripping.

## LINER:

A white, supercalendered glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 69 micron  $\pm$ 5%

Basic Weight 80 gsm  $\pm$ 5%

## SHELF LIFE:

3 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.