

Specification Sheet

BM632

GLOSS CLEAR STATIC PE 110MM

SELF CLING



FACE:

A highly transparent Polyethylene film. PE-Cling is printable by all conventional methods and gives good protection against scratching. Care should be taken with the use of heat for drying or UV curing.

Thickness 110 micron $\pm 10\%$

Basic weight 106 gsm $\pm 10\%$

ADHESIVE:

Clinging by intermolecular attraction without glue to most clean and glossy surfaces such as glass, PET, PVC and lacquered metal.

Warning: If UV Lamps are too high the static element of the material may fail and print receptivity will be effected.

Initial Tack

Final Adhesion

Min. App.Temp +5°C

Temp Range -20°C to +50°C

UV Resistance Good

The film complies with European Standard: 2002/95/EC (RoHS-hazardous substances 1/2003)

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 100 micron $\pm 7.5\%$

Basic Weight 114 gsm $\pm 7.5\%$

SHELF LIFE:

3 years when stored at 22° C / 50% RH (In original packaging)

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.