

Specification Sheet

BM656

MATT BLUE NON TRANSFER TE PET
NON-RESIDUE



FACE:

A matt blue non transfer tamper evident polyester. Once applied to a substrate, an irreversible "VOID / OPEN" message will activate in the face film if an attempt is made to remove it, thus providing unmistakable evidence of tampering. The material will remove from most substrates leaving no residue. The material is suitable for thermal transfer and all conventional printing methods.

Thickness 40 micron $\pm 5\%$
Basic weight

ADHESIVE:

A permanent acrylic resin pressure sensitive adhesive.

Initial Tack High
Final Adhesion Medium
Min. App.Temp $+5^{\circ}\text{C}$
Temp Range 0°C to $+80^{\circ}\text{C}$
UV Resistance Good

Whilst the minimum application temperature is $+5^{\circ}\text{C}$ it is recommended that labels are applied at a room temperature of 18°C .

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 90 micron $\pm 5\%$
Basic Weight 100 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.