

Specification Sheet

BM700
VELLUM 80
HIGH TACK



FACE:

A white, surface sized, super-calendered wood free printing paper. A basic general purpose, low cost paper suitable for a wide variety of applications.

Thickness 66 micron $\pm 5\%$
Basic weight 68 gsm $\pm 5\%$

ADHESIVE:

A high tack permanent acrylic adhesive with extremely high initial tack and adhesion on a wide variety of substrates including apolar, curved and slight rough surfaces. Suitable for labelling of chilled products.

Initial Tack High
Final Adhesion Very high
Min. App.Temp -5°C
Temp Range -40°C to $+70^{\circ}\text{C}$
UV Resistance Moderate

Complies with FDA 175.105 and with BgVV XXI recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised honey glassine paper, with high mechanical resistance to tearing.

Thickness 51 micron $\pm 5\%$
Basic Weight 57 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.