

# Specification Sheet

BM723A  
TWINSTICK  
PERMANENT



## FACE:

A supercalendered siliconised honey glassine paper, with high mechanical resistance to tearing.

Thickness 52 micron  $\pm 5\%$   
Basic weight 58 gsm  $\pm 5\%$

## ADHESIVE:

A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

The adhesive complies with FDA 175.105 and with BgVV recommendations for direct contact with dry and moist, non-fatty foodstuff.

Initial Tack High  
Final Adhesion High  
Min. App.Temp  $+5^{\circ}\text{C}$   
Temp Range  $-20^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$   
UV Resistance Excellent

**Middle layer:** A gloss clear polyester film. **Weight:** 33 gsm  $\pm 5\%$  **Thickness:** 23 micron  $\pm 5\%$

**Adhesive:** As above details.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 54 micron  $\pm 5\%$   
Basic Weight 61 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.