

Specification Sheet

BM729

TAMPER EVIDENT HDPE

PERMANENT



FACE:

A matt white tamper evident HDPE. The film will destruct by delamination if tampered with. Printable by all conventional methods including flexo, letterpress and thermal transfer printing.

Thickness 109 micron $\pm 5\%$

Basic weight 60 gsm $\pm 5\%$

ADHESIVE:

An extra permanent reinforced acrylic based adhesive with very good initial tack and adhesion on a wide range of substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -40°C to $+90^{\circ}\text{C}$

UV Resistance Good

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron $\pm 5\%$

Basic Weight 73 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.