

Specification Sheet

BM751

BRIGHT SILVER METALLISED FTP PET VOID
PERMANENT



FACE:

A bright, high gloss, metalized, polyester (PET) film. Surface treated for print receptivity. Reverse side silicone printed to facilitate the transfer of a small "void" footprint if a label is removed or tampered with after application.

Thickness 36 micron $\pm 5\%$
Basic weight 50 gsm $\pm 5\%$

ADHESIVE:

A permanent acrylic based adhesive with good adhesion to apolar substrates (e.g. PP and PE).

Initial Tack High
Final Adhesion High
Min. App.Temp -5°C
Temp Range -40°C to $+120^{\circ}\text{C}$
UV Resistance Good

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs. Also complies with FDA 175.105.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 77 micron $\pm 5\%$
Basic Weight 90 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.