

Specification Sheet

BM795

HOLOGRAPHIC PP- KALEIDOSCOPE
PERMANENT



FACE:

A bi-axially oriented bright design holographic polypropylene film with a print receptive top coat, laminated to paper.

Thickness 60 micron \pm 5%

Basic weight 70 gsm \pm 5%

ADHESIVE:

A rubber based, permanent adhesive. Excellent adhesive performance on a wide variety of substrates including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures, eg labelling of chilled products.

Initial Tack High

Final Adhesion Very high

Min. App.Temp +5°C

Temp Range -40°C to +70°C

UV Resistance Moderate

Adhesive complies with European food directives and legislation, FDA 175. 105 and the German recommendations XXI as published by BfR. BfR is the German Federal institute for Risk assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

LINER:

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

Thickness 56 micron \pm 5%

Basic Weight 62 gsm \pm 5%

SHELF LIFE:

2 years when stored at 22* C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.