

Specification Sheet

BM811

MATT WHITE LASER PE TESLIN
PERMANENT



FACE:

A matt white print receptive Polyolefin. Suitable for inkjet, laser and thermal transfer printing. It can also be foil stamped, embossed and is printable by all conventional methods such as offset, screen, gravure and flexo. It offers very good water and chemical resistance

Thickness 178 micron $\pm 10\%$
Basic weight 95 gsm $\pm 10\%$

ADHESIVE:

A permanent modified acrylic aqueous dispersion. This adhesive exhibits good resistance to light, heat and ageing.

Initial Tack Very High
Final Adhesion Very high
Min. App.Temp -5°C
Temp Range -30°C to $+150^{\circ}\text{C}$
UV Resistance Good

BS5609 Approved

Complies with USA Code of Federal Regulations recommendations for direct contact with dry and non-fatty foodstuff.

LINER:

A one side coated bleached kraft paper

Thickness 92 micron $\pm 9\%$
Basic Weight 87 gsm $\pm 6\%$

SHELF LIFE:

1 year when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.