

Specification Sheet

BF184
LINEN FSC
S2047N



FACE:

A white machine coated wood free printing paper with a woven appearance. Wet strength and fungicide treatments. This product is primarily used for the labelling of high and premium goods with a traditional image.

Thickness 106 micron $\pm 5\%$
Basic weight 90 gsm $\pm 5\%$

ADHESIVE:

A general purpose permanent rubber based adhesive for the wine industry.

Initial Tack High
Final Adhesion Very high
Min. App.Temp $+5^{\circ}\text{C}$
Temp Range -30°C to $+70^{\circ}\text{C}$
UV Resistance Poor

Complies with FDA 175.105 recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 61 micron $\pm 5\%$
Basic Weight 70 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.