

# Specification Sheet

BM1130

GLOSS WHITE PET (LV5567)

PERMANENT



## FACE:

Gloss white print receptive polyester that offers excellent dimensional stability combined with good solvent, humidity, elevated temperature and UV resistance. This is designed to accept conventional ink and thermal transfer printing with wax/resin ribbons. Typical applications include automotive, appliance, electronic and automotive.

Thickness 50 micron  $\pm 5\%$

Basic weight 33 gsm  $\pm 5\%$

## ADHESIVE:

A high performance permanent acrylic adhesive offering very good chemical, humidity and elevated temperature and UV resistance. Excellent adhesion on a broad range of surfaces.

Initial Tack High

Final Adhesion Very high

Min. App.Temp  $+4^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+149^{\circ}\text{C}$

UV Resistance Very good

UL Approved.

This product is in compliance with European parliament directive 2011/65/EU.

## LINER:

A blue polycoated glassine liner, one sided PE coated liner ensures adhesive smoothness. Suitable for high speed dispensing.

Thickness 76 micron  $\pm 5\%$

Basic Weight 96 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.