

Specification Sheet



BF905 NATUREFLEX CLEAR

S9500

FACE:

A gloss clear film specifically constructed to be biodegradable/compostable. With a print receptive top coating this material is printable by flexo and rotogravure printing.

Thickness 45 micron $\pm 5\%$

Basic weight 64 gsm $\pm 5\%$

ADHESIVE:

S9500 is an acrylic based biodegradable adhesive with good initial tack and adhesion on a wide variety of substrates.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -20°C to $+80^{\circ}\text{C}$

UV Resistance Moderate

Complies with the European food regulation 1935/2004/EC for direct food contact with dry, non-fatty foodstuff. Complies with DIN EN 13432 biodegradability and compostability regulation and is OK Compost certified under the tracking number S259.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 53 micron $\pm 5\%$

Basic Weight 60 gsm $\pm 5\%$

DIGITAL INFORMATION:

Total caliper

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.

Unit A2 Hubert Road, Brentwood, CM14 4JE

Tel: 01277 281 910 Fax:0800 085 6992

sales@bakermaterials.co.uk www.bakermaterials.co.uk

REGISTRATION NO. 1116854 IN ENGLAND

REGISTERED OFFICE:UNIT A2 HUBERT ROAD BRENTWOOD ESSEX CM14 4JE

VAT Registration No. GB 230 7578 65