Specification Sheet

BM1144 GLOSS CLEAR POLYESTER ULTRA REMOVABLE



FACE:

Gloss clear polyester face. Waterproof, tear, scuff and solvent resistance. Does not require an overlaminate. Gives clean removability from most surfaces. Suitable for toner/laser, thermal transfer, litho, flexo etc.

Typical applications include windscreen and retail signage.

Thickness 53 micron \pm 5% Basic weight 73 gsm \pm 5%

ADHESIVE:

A removable acrylic based adhesive. Excellent UV resistance, clarity and good weatherability are the main characteristics of this adhesive. Products with this adhesive are ideal for outdoor use.

Initial Tack Low

Final Adhesion Low

Min. App.Temp +5°C

Temp Range -40°C to +150°C

UV Resistance Good

LINER:

Kraft liner suitable for long print runs and larger sheet sizes for low to medium-speed printers

Thickness

Basic Weight 140 gsm ±5%

SHELF LIFE:

2 years when stored at 22* C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.