

# Specification Sheet

BM369

WBIJ SATIN WHITE PET  
PERMANENT - LOW TEMP



## FACE:

WBIJ satin white polyester with excellent cryogenic performance. The film is tear resistant and has good dimensional stability when exposed to variations in temp/humidity. The high performance coating enables good adhesion to high and low surface energy substrates

Thickness 85 micron  $\pm 5\%$   
Basic weight

## ADHESIVE:

A permanent modified acrylic aqueous dispersion, with very good chemical, humidity and UV resistance.

Initial Tack Good  
Final Adhesion Good  
Min. App.Temp  $+4^{\circ}\text{C}$   
Temp Range  $-196^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$   
UV Resistance Good

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 71 micron  $\pm 5\%$   
Basic Weight 71 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $25^{\circ}\text{C}$  / 55% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.