

Specification Sheet

BM1009

MATT SILVER VOID PET (02-261)

PAT 1



FACE:

A matt silver void polyester film with a selective release system for use in tamper evident labels. The coating gives excellent resistance to solvents, scuffing, moisture and ageing. Exceeding the face surface temperature may cause the void mechanism to fail.

Thickness 50 micron $\pm 10\%$

Basic weight

ADHESIVE:

A strong, permanent acrylic adhesive with proven performance for standard labels, nameplates and other similar uses. It has high cohesion and good resistance to heat, cold water and UV. It also has good quick-stick, peel and shear strength with excellent adhesion to low surface energy surfaces. It is designed for high speed automatic label application.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -30°C to $+149^{\circ}\text{C}$

UV Resistance Good

Automotive Approved.

UNDERWRITERS LABORATORY RECOGNITION

LINER:

A polycoated glassine liner.

Thickness 74 micron $\pm 10\%$

Basic Weight 82 gsm $\pm 10\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.