

# Specification Sheet

BM1071

GLOSS WHITE PET (01-870)

P116



## FACE:

A gloss white print receptive polyester which offers excellent dimensional stability combined with good solvent, humidity, elevated temperature and UV resistance. Designed to accept conventional ink and provides superior thermal transfer print quality with crisp definition at low burn temperatures with resin and wax/resin ribbons.

Thickness 50 micron  $\pm 10\%$

Basic weight

## ADHESIVE:

A permanent modified acrylic aqueous dispersion.

Initial Tack High

Final Adhesion High

Min. App.Temp  $+4^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+135^{\circ}\text{C}$

UV Resistance Good

Automotive approved.

## LINER:

A white polycoated glassine liner.

Thickness 74 micron  $\pm 10\%$

Basic Weight 82 gsm  $\pm 10\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.