

# Specification Sheet

BM1115

GLOSS CLEAR PET (01-700)

NPL



## FACE:

A gloss clear print receptive polyester which offers excellent optical clarity and dimensional stability combined with good solvent, humidity, elevated temperature and UV resistance. Designed to accept conventional inks and thermal transfer printing with resin and wax / resin ribbons.

Thickness 25 micron  $\pm 10\%$

Basic weight

## ADHESIVE:

An ultra clear UV stable permanent acrylic adhesive with excellent chemical, humidity and temperature resistance. Specially developed for clear film applications requiring excellent optical clarity, flow out properties and resistance to ooze. Standard overlaminating adhesive. Automotive approved.

Initial Tack Good

Final Adhesion Good

Min. App.Temp  $+4^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+135^{\circ}\text{C}$

UV Resistance Good

## UNDERWRITERS LABORATORY RECOGNITION

Automotive Approved.

## LINER:

A polycoated glassine liner.

Thickness 69 micron  $\pm 10\%$

Basic Weight 82 gsm  $\pm 10\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.