

Specification Sheet

BM1121

MATT WHITE DESTRUCT POLYOLEFIN (08
P1050



FACE:

A matt top coated white destructible polyolefin film which offers excellent printability by conventional inks and thermal transfer when used with resin and wax/resin ribbons. Designed specifically for security applications; once applied the label is extremely difficult to peel off and upon attempted removal, the material fractures easily preventing re-application.

Thickness 60 micron \pm 5%

Basic weight

ADHESIVE:

P1052 is a high performance adhesive offering very good adhesion to high and low surface energy surfaces. P1052 has very good temperature and humidity resistance.

Initial Tack High

Final Adhesion Very high

Min. App.Temp +4°C

Temp Range -30°C to +90°C

UV Resistance Moderate

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 55 micron \pm 5%

Basic Weight 55 gsm \pm 5%

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.