

Specification Sheet

BS7476



GLOSS WHITE PET
PERMANENT

FACE:

Gloss White aqueous coated polyester film. Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material

Thickness **53 micron ±5%**
Basic weight **74 gsm ±5%**

ADHESIVE:

Permanent acrylic pressure sensitive adhesive

Initial Tack **Good**
Final Adhesion **High**
Min. App.Temp **+5°C**
Temp Range **-20°C to +60°C**
UV Resistance **Excellent**

LINER:

A lightweight woodfree, white kraft paper, based on TFC pulp. For applications where good layflatness and dimensional stability are required. Suitable for converting rolls into sheets.

Thickness **90 micron ±5%**
Basic Weight **95 gsm ±5%**

SHELF LIFE:

1.5 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road,
Brentwood, Essex CM14 4JE

Sales
sales@bakermaterials.co.uk

Labels
01277 281900

Materials
01277 281910

BakPac
01277 281930

bakermaterials.co.uk

Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65