

# Specification Sheet

## BS7478



TEXTURED PET  
PERMANENT

### FACE:

Textured white Dry Toner print receptive PET label film. High toner bonding & scratch resistant No lamination required Permanent pressure sensitive adhesive. Water resistant.

Thickness                    **86 micron ±5%**  
Basic weight                **88 gsm ±5%**

### ADHESIVE:

Permanent pressure sensitive adhesive

Initial Tack                    **Good**  
Final Adhesion                **High**  
Min. App.Temp                **+5°C**  
Temp Range                    **-40°C to +80°C**  
UV Resistance                **Excellent**

### Attributes

- Unique haptic coating, High toner bonding & scratch resistant
- No lamination required
- Permanent pressure sensitive adhesive
- Waterresistant

### LINER:

A lightweight woodfree, white kraft paper, based on TFC pulp. For applications where good layflatness and dimensional stability are required. Suitable for converting rolls into sheets.

Thickness                    **120 micron ±5%**  
Basic Weight                **130 gsm ±5%**

### SHELF LIFE:

2 years when stored at 22\* C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road,  
Brentwood, Essex CM14 4JE

Sales  
sales@bakermaterials.co.uk

Labels  
01277 281900

Materials  
01277 281910

BakPac  
01277 281930

[bakermaterials.co.uk](http://bakermaterials.co.uk)

ESTABLISHED  
1973

Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65