

Specification Sheet

BF032



GLOSS WHITE PP TC
S692N

FACE:

A bi-axially oriented, gloss polypropylene film with a print receptive coating. Labels for non-squeezable containers, e.g cosmetics, toiletries, household chemicals, appliances, toys and car care products. Printable by most conventional printing methods such as Flexo, Letterpress and thermal transfer printing.

Thickness **58 micron \pm 5%**
Basic weight **50 gsm \pm 5%**

ADHESIVE:

S692N A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Initial Tack **High**
Final Adhesion **High**
Min. App.Temp **+5°C**
Temp Range **-20°C to +80°C**
UV Resistance **Excellent**

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness **53 micron \pm 5%**
Basic Weight **59 gsm \pm 5%**

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.



Unit A2, Hubert Road,
Brentwood, Essex CM14 4JE

Sales
sales@bakermaterials.co.uk

Labels
01277 281900

Materials
01277 281910

BakPac
01277 281930

bakermaterials.co.uk

Director: S R Baker. Company Reg No: 1116854 in England. Registered Office: Unit A2 Hubert Road, Brentwood, Essex CM14 4JE. VAT Reg No: GB 230 7578 65