

# Specification Sheet

BM598YE

GLOSS YELLOW PET 50MM PR

PERMANENT



## FACE:

A gloss yellow polyester (PET), surface treated to accept a high definition thermal transfer printing. Also printable by most conventional print methods including flexo and UV Letterpress.

Thickness 50 micron  $\pm 5\%$

Basic weight

## ADHESIVE:

A high tack, permanent, modified acrylic dispersion exhibiting good resistance to weather and UV with a high cohesive strength to a wide range of surfaces.

Initial Tack High

Final Adhesion Very high

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-20^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$

UV Resistance Very good

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 68 micron  $\pm 5\%$

Basic Weight 82 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.